

SEALER & COATING REMOVER

DESCRIPTION:

AQUA MIX SEALER & COATING REMOVER is a non-flammable, multi-purpose stripper formulated to stay wet longer which gives the product time to remove most sealers, epoxy grout haze, urethane coatings, synthetic finishes, adhesives, and paints. Also dissolves deep-set stains and removes heavy grease buildup.

USES:

Natural stone (such as granite, limestone, marble, slate, and travertine), ceramic, porcelain, grout, quarry, saltillo, terra cotta, cement pavers, and masonry surfaces.

TEST A SMALL AREA:

According to application instructions to determine desired results.

APPLICATION:

STRIPPING:

- 1) Read entire label before using.
- 2) SHAKE WELL before using.
- 3) Sweep or vacuum surface.
- 4) Apply a liberal amount of Sealer & Coating Remover to a small manageable area of up to 25 sq. ft. (2 m²).
- 5) Spread with a mop, sponge, or brush.
- 6) Allow product to dwell up to 1 hour without drying or until coating or residue softens. Do not allow Sealer & Coating Remover to dry on surface - if Remover starts to dry, add more to ensure surface is kept wet.
- 7) Agitate with a scrub brush or scrub machine.
- 8) Wipe up residue with clean, absorbent white cotton towels or sponge. A wet-dry vac may be used.
- 9) Removal of thick coatings or residue may require several applications - repeat steps 3 through 7 if coating is still on surface.
- 10) Rinse thoroughly with clean water.
- 11) Ready for surface traffic in 1 hour or after fumes have dissipated. Allow at least 24-hour drying time before applying AQUA MIX sealers and floor finishes.

EPOXY GROUT HAZE REMOVAL:

- 1) Read entire label before using.
- 2) SHAKE WELL before using.
- 3) Apply a minimal amount of Sealer & Coating Remover (just enough to make the surface damp) to a small manageable area of up to 25 sq. ft. (2 m²).
- 4) Spread with a mop, sponge, or brush.
- 5) Lightly agitate surface with a scrub brush until haze is removed. For large commercial installations, a white pad may be used with a scrub machine.
- 6) Mop up dirty solution.
- 7) Rinse thoroughly with clean water.
- 8) Ready for surface traffic in 1 hour or after fumes have dissipated. Allow at least 24-hour drying time before applying AQUA MIX sealers and floor finishes.

LIMITATIONS:

- Do not allow product to come in contact with any non-recommended surface.
- Do not spray. Do not use on resinous synthetic agglomerates.

HANDLING AND STORAGE:

- Close container after each use.
- Store in original container only.
- Store and use out of direct sunlight and in temperatures between 50 °F and 80 °F (10 °C and 27 °C).
- In case of spillage absorb with sawdust, sand, or clay litter.
- Dispose of residue or any unused leftover product in accordance with applicable federal, state, and local regulations.
- Unused, stored product is freeze-thaw stable.

CAUTION:

- KEEP OUT OF REACH OF CHILDREN.
- Contains aliphatic acid esters, surfactants, cleaning agents, and water. Use in well ventilated areas only.
- Avoid prolonged breathing of vapor and contact with eyes. Protect hands with household gloves and eyes with safety glasses.
- IF INGESTED: Do not induce vomiting. Drink 1 to 2 glasses of water. Seek immediate medical attention.
- EYE CONTACT: Flush with large amounts of water. If irritation persists, seek medical attention.
- SKIN CONTACT: Wash skin with soap and water. If irritation persists, seek medical attention.
- INHALATION: Relocate to fresh air. If symptoms persist, seek medical attention.

WARRANTY:

SATISFACTION GUARANTEED. If not completely satisfied with this product's performance, when used as directed, contact Aqua Mix for exclusive remedy of either refund of purchase price or replacement of product upon return of unused portion with proof of purchase within one year of purchase. Determining suitability of product for any intended purpose shall be solely the responsibility of the user. THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE, WHICH EXTEND BEYOND THE DESCRIPTION ON THIS LABEL. IN NO EVENT SHALL AQUA MIX BE LIABLE TO THE CUSTOMER OR ANYONE ELSE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, HOWEVER OCCASIONED. ALWAYS TEST FIRST.

COVERAGE:

Approximately 75 to 200 sq. ft. (7 m² to 20 m²) per gallon (3.785 L).

ORDERING INFORMATION:

Item Code US	Item Code Canada	Size	Package
010262	100011	1 Qt.	Bottle
010263	100012	1 Gal.	Bottle
010264	TBD	5 Gal.	Pail
010265	n/a	55 Gal.	Drum