

# SEALER'S CHOICE® GOLD

## DESCRIPTION:

AQUA MIX SEALER'S CHOICE® GOLD is a premium, no-sheen, natural-look, Low VOC, **water-based**, penetrating sealer formulated to provide maximum stain protection, especially in food preparation and serving areas. May also be used as a pre-grouting sealer. Allows moisture vapor transmission. It is also an excellent grout sealer. The NEW Rapid Cure Formula protects in less than 4 hours and is designed to achieve optimal penetration into dense, low-porosity surfaces.

Aqua Mix Low VOC (Volatile Organic Compound) formulas help provide better indoor and outdoor air quality compared to similar traditional products. 47 grams of VOC's per liter of material.

## USES:

- All natural stone (such as marble, granite, slate, travertine, and limestone), porcelain, quarry, Saltillo, terra cotta, cement pavers, masonry surfaces, and other porous tile and grout where a natural look is desired.
- Effective for interior and exterior applications.

## EXPECTED WEAR UP TO 15 YEARS:

- Will vary depending on hardness and texture of surface, type of area, surface wear, frequency, and type of maintenance products used.
- Weather conditions, harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners will affect wear.

## TEST A SMALL AREA:

According to application instructions with a 24-hour cure time to determine desired results. Test for stain repellency using likely contaminants.

## APPLICATION:

- 1) Read entire label before using.
- 2) For new installations, sealer can be applied as soon as 48 hours after grouting.
- 3) Surface must be clean, dry, and free of existing sealers or coatings.
- 4) Apply using a sponge, brush, paint pad, cotton towel, or sprayer.  
NOTE: Be sure any sealer that does not penetrate surface is removed from surface within 5 minutes of each application using absorbent paper or cotton towels.
- 5) If 2 or more coats are applied, allow a minimum of 30 minutes drying time between coats.
- 6) 2 hours after final coat conduct a test to determine if surface is completely sealed by applying water droplets to the surface. If water is absorbed, apply an additional coat. Wait 2 hours and repeat the test.
- 7) Ready for surface traffic in 2 hours after final coat. Keep area dry for 12 hours. Achieves a full cure in 24 hours.
- 8) Clean applicator tools with water after each use.

## PRE-GROUTING APPLICATION:

- Apply over clean stone or tile a minimum of 2 hours prior to grouting - follow application procedures above.

## MAINTENANCE:

- Concentrated Stone & Tile Cleaner or
- AquaKleen™ is recommended for routine spray and wipe cleaning.
- AquaShield™ is recommended for routine spray and wipe cleaning & resealing.

## LIMITATIONS:

- Do not allow sealer to come in contact with any non-recommended surface.
- May slightly lighten or darken some surfaces.
- Sealer will not prevent surface wear or etching from acids or caustic chemicals.

## HANDLING AND STORAGE:

- Close container after each use.
- Store in original container only.
- Store and use between temperatures of 40 °F - 90 °F (4 °C - 32 °C).

## CAUTION:

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains glycol ether monobutyl ether. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.

## KEEP OUT OF REACH OF CHILDREN

**LIMITED PRODUCT WARRANTY** Custom Building Products ("Custom") warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's printed instructions. Custom makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another.

## COVERAGE:

Approximately 300 - 1,500 sq. ft. (30 m<sup>2</sup> - 139 m<sup>2</sup>) per coat per gallon (3.8 L), depending on type of stone, tile, porosity and texture of surface, temperature, humidity, and method of application.

## ORDERING INFORMATION:

Item Code US	Item Code Canada	Size	Package
030881	C030881	1 Pt. (473 ml)	Bottle
030882-4	C030882-4	1 Qt. (946 ml)	Bottle
030883	C030883	1 Gal. (3.8 L)	Bottle
030884	C030884	5 Gal. (19 L)	Pail