

GROUT COLORANT

DESCRIPTION:

AQUA MIX GROUT COLORANT is an easy-to-use waterborne epoxy that re-colors, seals and rejuvenates existing grout joints. Also simplifies ongoing grout cleaning.

USES:

Sanded, un-sanded and epoxy grout joints. Effective for interior and exterior applications.

TEST A SMALL AREA:

According to application instructions, with a minimum 1-hour cure time to determine desired results.

EXPECTED WEAR:

Will vary depending on hardness and texture of surface, type of area, surface wear, frequency, and type of maintenance products used. The expected wear is up to 15 years. Weather conditions, harsh cleaning methods and high-alkaline, acidic or solvent-based cleaners will affect wear.

APPLICATION:

- 1) Read entire label before using.
- 2) SHAKE WELL before using.
- 3) For new installations, Grout Colorant can be applied as soon as 48 hours after grouting.
- 4) Grout joints must be clean, dry and free of existing sealers or coatings.
- 5) Prepare existing grout joints: MOST TILE & STONE: Use Aqua Mix Grout Colorant Pre-Treat Cleaner or Aqua Mix Phosphoric Acid Cleaner. ACID-SENSITIVE STONE: Use Aqua Mix Heavy Duty Tile & Grout Cleaner EPOXY GROUT JOINTS: Use Aqua Mix Sealer & Coating Remover.
- 6) If more than 1 bottle of a single color is to be used, mix the material together in a large container to ensure uniformity of color.
- 7) If using Grout Colorant Applicator, pour Grout Colorant into Applicator bottle and apply a bead onto grout joint.
- 8) Spread evenly using the Applicator Brush or toothbrush, working Grout Colorant into joint using a back-and-forth motion. Thin, even coats should be applied, limiting the amount of Grout Colorant that gets on the tile.
- 9) If going from a dark to light grout color, more than 1 application may be necessary with a minimum 2-hour drying time between coats.
- 10) After Grout Colorant has dried 1 or more hours (never more than 12 hours), lightly mist surface with water and let stand 5 minutes. Remove excess Grout Colorant from surface of tile using water and a white nylon scrub pad.
- 11) Ready for surface traffic in 2 hours. Keep area dry for at least 24 hours. Avoid direct scrubbing on grout joints for 20 days to allow a full cure.
- 12) Clean applicator tools with water after each use.

LIMITATIONS:

- Grout Colorant is not recommended for use under water in pools, ponds, or on areas subject to hydrostatic pressure..
- Do not use solvent-based cleaners on re-colored grout joints.
- Previously applied sealers, with the exception of Aqua Mix Penetrating Sealer, Aqua Mix Grout Sealer, Aqua Mix Pro-Solv, Aqua Mix Ultra-Solv or Aqua Mix Sealer's Choice Gold, must be removed to provide a bondable surface. Aqua Mix Sealer & Coating Stripper is recommended for this procedure.
- Porous tile may require sealing to ensure colorant is not absorbed into the tile.

HANDLING AND STORAGE:

- Close container after each use.
- Store in original container only.
- Use in temperatures between 50°F and 80°F (10° C and 27° C).
- Unused, stored product is freeze-thaw stable.

CAUTION:

- KEEP OUT OF REACH OF CHILDREN.
- Do not take internally.
- Avoid contact with eyes. Gloves and eye protection should be worn during application.
- IF INGESTED: Drink 1 to 2 glasses of water. If symptoms persist, seek medical attention.
- EYE AND SKIN CONTACT: Flush thoroughly with water. If irritation persists, seek medical attention.

WARRANTY:

SATISFACTION GUARANTEED. If not completely satisfied with this product's performance, when used as directed, contact Aqua Mix for exclusive remedy of either refund of purchase price or replacement of product upon return of unused portion with proof of purchase within one year of purchase. Determining suitability of product for any intended purpose shall be solely the responsibility of the user. THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE, WHICH EXTEND BEYOND THE DESCRIPTION ON THIS LABEL. IN NO EVENT SHALL AQUA MIX BE LIABLE TO THE CUSTOMER OR ANYONE ELSE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, HOWEVER OCCASIONED. ALWAYS TEST FIRST.

COVERAGE:
 Approximately 50 to 300 sq. ft. (5 m² to 28 m²) per 8-oz (237 ml) bottle depending on width and porosity of grout joint, size of tile, and method of application.

ORDERING INFORMATION:

Item Code US	Item Code Canada	Color
063001	064001	White
063002	064002	Antique White
063003	064003	Linen White
063004	064004	Navajo
063005	064005	Buff
063006	064006	Sand
063007	064007	Beige
063008	064008	Wheat
063009	064009	Cinnamon
063010	064010	Cocoa
063011	064011	Light Gray
063012	064012	Cadet Blue
063013	064013	Rose
063014	064014	Black
063015	064015	Bright White
063016	064016	Canvas
063017	064017	Smoke
063018	064018	Mauve
063019	064019	Evergreen
063020	064020	Teal
063021	064021	Silver
063022	064022	Natural Gray
063023	064023	Pewter
063024	064024	Charcoal Gray
063025	064025	Pure White