

Adoquin/Cantera Stone

Pre-Grouting Sealing

Purpose: To protect porous stone from grout staining and ease grout clean-up.

| Desired Result | Product Options | # of Coats | Approx. Coverage Per/Coat Per/Gal (3.8 L) | Cure Time Prior To Grouting | Int. | Ext. | Notes |
|---|-----------------------------------|------------|---|-----------------------------|------|------|--|
| Premium No-Sheen Natural Look | Sealer's Choice® Gold Ultra-Solv® | 1 | 300 sq.ft. (28m ²) | 2 hours | Yes | Yes | Recommended for maximum stain protection when a no-sheen, natural look is required. |
| Economical No-Sheen Natural Look | Penetrating Sealer Pro-Solv® | 1 | 300 sq.ft. (28m ²) | 2 hours | Yes | Yes | Provides more limited protection than premium sealers. |
| Low-Medium Sheen | Seal & Finish Low Sheen | 1 | 300 sq.ft. (28m ²) | 2 hours | Yes | Yes | Easy reapplication. No stripping necessary. Excellent stain protection. |
| High-Sheen (Interior Only) | High-Gloss Sealer | 1 | 300 sq.ft. (28m ²) | 2 hours | Yes | No | Easy reapplication. |
| Premium No-Sheen Darkened Color Enhancement | Enrich'N'Seal™ | 1 | 400 sq.ft. (37m ²) | 2 hours | Yes | Yes | Use only on unsealed stone surfaces. Critical to test for desired look as darkening is non-reversible. |
| Economical No-Sheen Darkened Color Enhancement | Stone Enhancer | 1 | 400 sq.ft. (37m ²) | 2 hours | Yes | Yes | Use only on unsealed stone surfaces. Test for desired look as darkening is non-reversible. |

Sealing/Finishing

Purpose: To protect porous stone from sub-surface staining and ease ongoing maintenance.

| Desired Result | Product Options | # of Coats | Approx. Coverage Per/Coat Per/Gal (3.8 L) | Grout Cure Time Prior To Sealing | Expected Wear | Int. | Ext. | Notes |
|---|-----------------------------------|------------|--|----------------------------------|-----------------------------|------|------|---|
| Premium No-Sheen Natural Look | Sealer's Choice® Gold Ultra-Solv® | 2 | 400 - 600 sq.ft. (35m ² -55m ²) | 48 hours | Up to 15 Yrs | Yes | Yes | Recommended for maximum stain protection when a no-sheen, natural look is required. |
| Economical No-Sheen Natural Look | Penetrating Sealer Pro-Solv® | 2 | 400 - 600 sq.ft. (35m ² -55m ²) | 48 hours | Up to 5 Yrs Up to 10 Yrs | Yes | Yes | Provides more limited protection than premium sealers. |
| Low-Medium Sheen | Seal & Finish Low Sheen | 3-4 | 400 - 600 sq.ft. (35m ² -55m ²) | 48 hours | Up to 3 Yrs | Yes | Yes | Easy reapplication. No stripping necessary. Excellent stain protection. |
| High-Sheen (Interior Only) | High-Gloss Sealer | 3-4 | 400 - 600 sq.ft. (35m ² -55m ²) | 48 hours | Up to 3 Yrs | Yes | No | Easy reapplication. |
| Premium No-Sheen Darkened Color Enhancement | Enrich'N'Seal™ | 1-2 | 500 - 1,000 sq. ft. sq.ft. (45m ² -95m ²) | 48 hours | Up to 15 Yrs | Yes | Yes | Use only on unsealed stone - seals the surface as it darkens. Critical to test for desired look as darkening is non-reversible. |
| Economical No-Sheen Darkened Color Enhancement | Stone Enhancer | 1-2 | 500 - 1,000 sq. ft. sq.ft. (45m ² -95m ²) | 48 hours | Up to 5 Yrs | Yes | Yes | Use only on unsealed stone - seals the surface as it darkens. Test for desired look as darkening is non-reversible. |

Maintenance

Purpose: To safely maintain a clean stone and grout surface and to preserve the stone's beauty and integrity.

| Type of Maintenance | Product Options | Dilution Ratio | Expected Coverage Per Gallon (3.8L) | Notes |
|---|---|--|---|--|
| Routine | Concentrated Stone & Tile Cleaner AquaKleen™ | 1-4oz./gallon of water (30-118ml/3.785L) Use undiluted | 10,000-20,000 sq.ft. (930m ² -1,860m ²) | Highly-concentrated. Neutral pH. For regular use. Quick spray and wipe cleaning. |
| Periodic Heavy-Duty | Stone Deep Clean Heavy Duty Tile & Grout Cleaner | Add up to 4 parts water | 500 sq. ft. - 600 sq. ft. (45m ² -55m ²) | Contains no acid. Safe on stone, grout and mortar. |
| Periodic Heavy-Duty Large Commercial Areas | 1&2 Deep Clean | 1/4 to 1/2 cup (60-120ml) of powder and liquid to 2 1/2 gallons (10L) of water | 8,000 - 32,000 sq. ft. (743m ² -.973m ²) | Recommended for large commercial floor applications. |

Always refer to product Data Sheets for complete application, use, safety, limitation and warranty information.

Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.