

# Agglomerate Stone/Cement

## Pre-Grouting Sealing

**Purpose:** To protect Agglomerate Stone/Cement from grout staining and ease grout clean-up

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Cure Time Prior To Grouting	Int.	Ext.	Notes
<b>Premium No-Sheen Natural Look</b>	Sealer's Choice® Gold Ultra-Solv®	1	1,000 sq.ft. (95m <sup>2</sup> )	2 hours	Yes	Yes	Recommended in food preparation or serving areas for maximum stain protection when a no-sheen, natural look is required.
<b>Economical No-Sheen Natural Look</b>	Penetrating Sealer Pro-Solv®	1	1,000 sq.ft. (95m <sup>2</sup> )	2 hours	Yes	Yes	Provides limited protection in food preparation and serving areas.
<b>Premium Darkened Color Enhancement</b>	Enrich'N'Seal™	1	1,200 sq. ft. (115m <sup>2</sup> )	2 hours	Yes	Yes	Recommended on porous, unsealed surfaces. Sealer darkens. Critical to test for desired results as darkening is non-reversible.
<b>Economical Darkened Color Enhancement</b>	Stone Enhancer	1	1,200 sq. ft. (115m <sup>2</sup> )	2 hours	Yes	Yes	Recommended on porous, unsealed surfaces. Sealer darkens. Critical to test for desired results as darkening is non-reversible.

**Note** Most epoxy-bodied terrazzo is impervious and will not accept a sealer.

## Terrazzo (Sealing)

**Purpose:** To protect porous stone from sub-surface staining and ease ongoing maintenance.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Grout Cure Time Prior To Sealing	Expected Wear	Int.	Ext.	Notes
<b>Premium No-Sheen Natural Look</b>	Sealer's Choice® Gold Ultra-Solv®	1-2	1,000 - 1,200 sq.ft (95m <sup>2</sup> -110m <sup>2</sup> )	48 hours	Up to 15 Yrs	Yes	Yes	Recommended for max stain protection when a natural look is required.
<b>Economical No-Sheen</b>	Penetrating Sealer Pro-Solv®	1-2	1,000 - 1,200 sq.ft. (95m <sup>2</sup> -110m <sup>2</sup> )	48 hours	Up to 5 Yrs Up to 10 Yrs	Yes	Yes	Provides more limited protection than premium sealers.
<b>Premium No-Sheen Darkened Color Enhancement</b>	Enrich'N'Seal™	1	1,500 sq.ft. (140m <sup>2</sup> )	48 hours	Up to 15 Yrs	Yes	Yes	Use only on unsealed terrazzo - seals the surface as it darkens. Test for desired look as darkening is non-reversible.
<b>Economical No-Sheen Darkened Color Enhancement</b>	Stone Enhancer	1	1,500 sq.ft. (140m <sup>2</sup> )	48 hours	Up to 5 Yrs	Yes	Yes	Use only on unsealed terrazzo - seals the surface as it darkens. Critical to test for desired look as darkening is non-reversible.

## Maintenance

**Purpose:** To safely maintain a clean stone and grout surface and to preserve the stone's beauty and integrity.

Type of Maintenance	Product Options	Dilution Ratio	Expected Coverage Per Gallon (3.8 L)	Notes
<b>Routine</b>	Concentrated Stone & Tile Cleaner AquaKleen™	1-4oz./gallon of water (30-118ml/3.785L) Use undiluted	10,000-20,000 sq.ft. (930m <sup>2</sup> -1,860m <sup>2</sup> )	Highly-concentrated. Neutral pH. For regular use. Quick spray and wipe cleaning.
<b>Routine Countertops &amp; Walls</b>	Stone Clean & Shine Brilliance®	Use undiluted	N/A	Designed to clean & polish - helps maintain factory shine. Not for floors.
<b>Periodic Heavy-Duty</b>	Stone Deep Clean Heavy-Duty Tile & Grout Cleaner	Add up to 4 parts water	500 sq. ft. - 600 sq. ft. (45m <sup>2</sup> -55m <sup>2</sup> )	Contains no acid. Safe on stone and grout/mortar. Removes wax-type finishes.
<b>Periodic Heavy-Duty Large Commercial Areas</b>	1&2 Deep Clean	1/4 to 1/2 cup (60-120ml) of powder and liquid to 2 1/2 gallons (10L) of water	8,000 - 32,000 sq. ft. (743m <sup>2</sup> -2,973m <sup>2</sup> )	Recommended for large commercial floor applications.

**Note:** Heavy-duty alkaline cleaners will remove wax-type finishes.

Always refer to product Data Sheets for complete application, use, safety, limitation and warranty information.  
Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.