

# Brick Pre-Grouting Sealing

**Purpose:** To protect porous brick from grout staining and ease grout clean-up.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Cure Time Prior To Grouting	Int.	Ext.	Notes
<b>Temporary Grouting Protection</b>	Grout Release	1-2	300-600 sq.ft. (25m <sup>2</sup> -55m <sup>2</sup> )	2 hours	Yes	Yes	Use as a temporary aide to facilitate grouting process on wire-cut or rough, textured surface.
<b>Premium No-Sheen Natural Look</b>	Sealer's Choice® Gold Ultra-Solv®	1	400 sq.ft. (35m <sup>2</sup> )	2 hours	Yes	Yes	Recommended for maximum stain protection when a no-sheen, natural look is required.
<b>Economical No-Sheen Natural Look</b>	Penetrating Sealer Pro-Solv®	1	400 sq.ft. (35m <sup>2</sup> )	2 hours	Yes	Yes	Provides more limited protection than premium sealers.
<b>Low-Medium Sheen</b>	Seal & Finish Low Sheen	1	400 sq.ft. (35m <sup>2</sup> )	2 hours	Yes	Yes	Easy reapplication. No stripping necessary. Excellent stain protection.
<b>High-Sheen (Interior Only)</b>	High-Gloss Sealer	1	400 sq.ft. (35m <sup>2</sup> )	2 hours	Yes	No	Easy reapplication.
<b>Premium No-Sheen Darkened Color Enhancement</b>	Enrich'N'Seal™	1	500 sq.ft. (45m <sup>2</sup> )	2 hours	Yes	Yes	Use only on unsealed brick surfaces. Test for desired look as darkening is non-reversible.
<b>Economy No-Sheen Darkened Color Enhancement</b>	Stone Enhancer	1	500 sq.ft. (45m <sup>2</sup> )	2 hours	Yes	Yes	Use only on unsealed brick surfaces. Test for desired look as darkening is non-reversible.

## Sealing/Finishing

**Purpose:** To protect porous brick from sub-surface staining and ease ongoing maintenance.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Grout Cure Time Prior To Sealing	Expected Wear	Int.	Ext.	Notes
<b>Premium No-Sheen Natural Look</b>	Sealer's Choice® Gold Ultra-Solv™	2	400 - 600 sq.ft. (35m <sup>2</sup> -55m <sup>2</sup> )	48 hours	Up to 15 Yrs	Yes	Yes	Recommended for maximum stain protection when a no-sheen, natural look is required.
<b>Economical No-Sheen Natural Look</b>	Penetrating Sealer Pro-Solv®	2	400 - 600 sq.ft. (35m <sup>2</sup> -55m <sup>2</sup> )	48 hours	Up to 5 Yrs Up to 10 Yrs	Yes	Yes	Provides more limited protection than premium sealers.
<b>Low-Medium Sheen</b>	Seal & Finish Low Sheen	2-3	400 - 600 sq.ft. (35m <sup>2</sup> -55m <sup>2</sup> )	48 hours	Up to 3 Yrs	Yes	Yes	Easy reapplication. No stripping necessary. Excellent stain protection.
<b>High-Sheen (Interior Only)</b>	High-Gloss Sealer	2-3	400 - 600 sq.ft. (35m <sup>2</sup> -55m <sup>2</sup> )	48 hours	Up to 3 Yrs	Yes	No	Easy reapplication.
<b>Premium No-Sheen Darkened Color Enhancement</b>	Enrich'N'Seal™	1-2	500 - 1,000 sq. ft. sq.ft. (45m <sup>2</sup> -95m <sup>2</sup> )	48 hours	Up to 15 Yrs	Yes	Yes	Use only on unsealed brick - seals the surface as it darkens. Critical to test for desired look as darkening is non-reversible.
<b>Economical No-Sheen Darkened Color Enhancement</b>	Stone Enhancer	1-2	500 - 1,000 sq. ft. sq.ft. (45m <sup>2</sup> -95m <sup>2</sup> )	48 hours	Up to 5 Yrs	Yes	Yes	Use only on unsealed brick - seals the surface as it darkens. Test for desired look as darkening is non-reversible.

## Maintenance

**Purpose:** To safely maintain a clean brick and grout/mortar surface and to preserve the stone's beauty and integrity.

Type of Maintenance	Product Options	Dilution Ratio	Expected Coverage Per Gallon (3.8 L)	Notes
<b>Routine</b>	Concentrated Stone & Tile Cleaner	1-4oz./gallon of water (30-118ml/3.785L)	10,000-20,000 sq.ft. (930m <sup>2</sup> -1,860m <sup>2</sup> )	Highly-concentrated. Neutral pH. For regular use.
<b>Periodic Heavy-Duty</b>	Heavy-Duty Tile & Grout Cleaner Stone Deep Clean	Add up to 4 parts water	500 sq. ft. - 600 sq. ft. (45m <sup>2</sup> -55m <sup>2</sup> )	Contains no acid. Safe on brick and grout/mortar.
<b>Periodic Heavy-Duty Large Commercial Areas</b>	1&2 Deep Clean	1/4 to 1/2 cup (60-120ml) of gallons (10L) of water	8,000 - 32,000 sq. ft. (743m <sup>2</sup> -2,973m <sup>2</sup> )	Recommended for large commercial floor applications.

Always refer to product Data Sheets for complete application, use, safety, limitation and warranty information.  
Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.