

# Ceramic Tile Textured/Unglazed

## Crazed Glaze Pre-Grouting Protection

**Purpose:** To protect pitted or crazed glaze ceramic tile from grout staining and ease grout clean-up.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Cure Time Prior To Grouting	Int.	Ext.	Notes
Temporary Grouting Protection	Floor Shine & Hardener	1	1,000 sq. ft (95 m <sup>2</sup> )	2 hours	Yes	No	Grout Manufacturer's recommended cleanup should remove Floor Shine & Hardener at time of grout clean-up

**Helpful tip:** Add Aqua Mix Grout Haze Clean-Up to last bucket of clean water used in grout clean-up. This will facilitate removal of remaining grout residue on surface.

## Interior Areas Only High-Sheen Finishing

**Purpose:** To create a surface sheen on rough-textured finish Ceramic Tile - Interior areas only.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Grout Cure Time Prior To Sealing	Expected Wear	Int.	Ext.	Notes
High-Sheen Finish	High-Gloss Sealer	1-2	800-1,000 sq. ft. (75m <sup>2</sup> -95m <sup>2</sup> )	48 hours	Up to 3 Yrs	Yes	No	Rough/textured interior surfaces only. Easy reapplication.

## Sealing/Finishing

**Purpose:** To safely maintain a clean stone and grout surface and to preserve the stone's beauty and integrity.

Type of Maintenance	Product Options	Dilution Ratio	Expected Coverage Per Gallon (3.8 L)	Notes
Routine	Concentrated Stone & Tile Cleaner AquaKleen™	1-4oz./gallon of water (30-118ml/3.785L) Use undiluted	10,000-20,000 sq.ft. (930m <sup>2</sup> -1,860m <sup>2</sup> )	Highly-concentrated. Neutral pH. For regular use. Quick spray and wipe cleaning.
Periodic Heavy-Duty	Heavy-Duty Tile & Grout Cleaner Stone Deep Clean	Add up to 4 parts water	500 sq. ft. - 600 sq. ft. (45m <sup>2</sup> -55m <sup>2</sup> )	Contains no acid. Safe on tile and grout/mortar. Will remove floor finishes.
Periodic Heavy-Duty Large Commercial Areas	1&2 Deep Clean	1/4 to 1/2 cup (60-120ml) powder and liquid to 2 1/2 gallons of water.	8,000 - 32,000 sq. ft. (743m <sup>2</sup> -2,973m <sup>2</sup> )	Recommended for large commercial floor applications. Will remove floor finishes.

Always refer to product Data Sheets for complete application, use, safety, limitation and warranty information.  
Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.