

# Grout - Porous

## Sealing

**Purpose:** To protect porous grout associated with glazed ceramic from sub-surface staining and ease ongoing maintenance.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal	Grout Cure Time Prior (3.8 L)	Expected Wear To Sealing	Int.	Ext.	Notes
<b>Premium No-Sheen Natural Look</b>	Sealer's Choice® Gold Ultra-Solv®	1-2	1,000-3,000 sq.ft. (95m <sup>2</sup> -280m <sup>2</sup> )	48 hours	Up to 15 Yrs	Yes	Yes	All grout, with the exception of 100% epoxy grout, is porous and needs to be sealed for optimal stain protection.
<b>Economical No-Sheen Natural Look</b>	Grout Sealer	1-2	1,500-3,000 sq.ft. (140m <sup>2</sup> -280m <sup>2</sup> )	48 hours	Up to 5 Yrs	Yes	Yes	
<b>Economical No-Sheen</b>	SameDay™ Grout Sealer	1-2	300-500 sq. ft./15oz. (28m <sup>2</sup> -46m <sup>2</sup> )/144 ml	Min. 2 hours	1-2 Yrs	Yes	Yes	Designed for quick spray applications.
<b>Premium No-Sheen Darkened Color Enhancement</b>	Enrich'N'Seal™	1-2	1,000-3,000 sq.ft. (95m <sup>2</sup> -280m <sup>2</sup> )	48 hours	Up to 15 Yrs	Yes	Yes	Use to darken and seal faded unsealed grout. Critical to test for desired look as darkening is non-reversible.
<b>Economical No-Sheen Darkened Color Enhancement</b>	Stone Enhancer	1-2	1,000-3,000 sq.ft. (95m <sup>2</sup> -280m <sup>2</sup> )	48 hours	Up to 5 Yrs	Yes	Yes	Use to darken and seal faded unsealed grout. Critical to test for desired look as darkening is non-reversible.
<b>Re-Coloring</b>	Grout Colorant	1-2	50 - 400 sq. ft (8 -oz) (5m <sup>2</sup> -35m <sup>2</sup> )	48 hours	Up to 15 Yrs	Yes	Yes	Use to provide even color or change color of existing grout. Also provides premium seal.

**Note:** 100% solid epoxy grout does not require a sealer.

If tile/stone used is porous, grout should be sealed at same time using sealer selected for tile/stone.

## Grout Maintenance

**Purpose:** To safely maintain a clean grout and tile/stone surface and to preserve the installation's beauty and integrity.

Type of Maintenance	Product Options	Dilution Ratio	Expected Coverage Per Gallon (3.8 L)	Notes
<b>Routine</b>	Concentrated Stone & Tile Cleaner AquaKleen™	1-4oz./gallon of water (30-118ml/3.785L) Use undiluted	10,000-20,000 sq.ft. (930m <sup>2</sup> -1,860m <sup>2</sup> )	Highly-concentrated. Neutral pH. For regular use. Quick spray and wipe cleaning.
<b>Periodic Heavy-Duty Floors</b>	Heavy-Duty Tile & Grout Cleaner Stone Deep Clean	Add up to 4 parts water	500 - 600 sq. ft. (45m <sup>2</sup> -55m <sup>2</sup> )	Contains no acid. Safe on tile and grout/mortar. Will remove floor finishes.
<b>Periodic Heavy-Duty Countertops, Walls &amp; Floors</b>	Grout Deep Clean	Use undiluted	N/A	Excellent spray applicaiton for neglected grout joints. Contains no acid.

Always refer to product Data Sheets for complete application, use, safety, limitation and warranty information.

Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.