

Porcelain Tile (Unglazed)

Polished & Unpolished Pre-Grouting Sealing

Purpose: To protect unglazed polished and honed porcelain tile from grout staining and ease grout clean-up.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Cure Time Prior To Grouting	Int.	Ext.	Notes
Premium No-Sheen Natural Look	Ultra-Solv®	1	800 - 1,200 sq.ft. (75m ² - 115m ²)	2 hours	Yes	Yes	Important to ensure 100% coverage over tile surface. Polish dry any sealer that remains on tile surface within 5 minutes after application.
Economical No-Sheen Natural Look	Pro-Solv®	1	800 sq.ft. (75m ²) (75m ² - 115m ²)	2 hours	Yes	Yes	

Textured Surface Pre-Grouting Sealing

Purpose: To protect unglazed, textured porcelain tile from grout staining and ease grout clean-up.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Cure Time Prior To Grouting	Int.	Ext.	Notes
Temporary Grouting Protection	Floor Shine & Hardener	1	1,000 sq.ft. (95m ²)	2 hours	Yes	No	Grout Manufacturer's recommended cleanup should remove Floor Shine & Hardener at time of grout clean-up.

High-Sheen Finish

Purpose: To protect unglazed, textured porcelain tile from grout staining and ease grout clean-up.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Cure Time Prior To Grouting	Int.	Ext.	Notes
High-Sheen Finish	High-Gloss Sealer	1-2	700 - 800 sq.ft. (65m ² - 75m ²)	Up to 3 hours	Yes	No	Rough/textured interior surfaces only. Easy reapplication.

Note: High alkaline cleaners will remove High-Gloss Sealer.

Sealing

Purpose: To protect unglazed porcelain from sub-surface staining and ease ongoing maintenance.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Cure Time Prior To Grouting	Expected Wear	Int.	Ext.	Notes
Premium No-Sheen Natural Look	Ultra-Solv®	1	1,500 sq.ft. (140m ²)	48 hours	Up to 15 Yrs.	Yes	Yes	Recommended for maximum stain protection when a no-sheen, natural look is required.
Economical No-Sheen Natural Look	Pro-Solv®	1	1,500 sq.ft. (140m ²)	48 hours	Up to 15 Yrs	Yes	Yes	Provides more limited protection than premium sealers.

Maintenance

Purpose: To safely maintain a clean stone and grout surface and to preserve the tile's beauty and integrity.

Type of Maintenance	Product Options	Dilution Ratio	Expected Coverage Per Gallon (3.8 L)	Notes
Routine	Concentrated Stone & Tile Cleaner AquaKleen™	1-4oz./gallon of water (30-118ml/3.785L) Use undiluted	10,000-20,000 sq.ft. (930m ² -1,860m ²)	Highly-concentrated. Neutral pH. For regular use. Quick spray and wipe cleaning.
Periodic Heavy-Duty	Heavy-Duty Tile & Grout Cleaner Stone Deep Clean	Add up to 4 parts water	500 - 600 sq. ft. (45m ² -55m ²)	Contains no acid. Safe on tile and grout/mortar
Periodic Heavy-Duty Large Commercial Areas	1 & 2 Deep Clean	1/4 to 1/2 cup (60 - 120 ml)	8,000 - 32,000 sq. ft. (743m ² -2,973m ²)	Recommended for large commercial floor applications.

Always refer to product Data Sheets for complete application, use, safety, limitation and warranty information.
Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.