

Quarry Tile

Pre-Grouting Sealing

Purpose: To protect porous tile from grout staining and ease grout clean-up.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Cure Time Prior To Grouting	Int.	Ext.	Notes
Premium No-Sheen Natural Look	Sealer's Choice® Gold Ultra-Solv®	1	700 sq.ft. (65m ²)	2 hours	Yes	Yes	Recommended for maximum stain protection when a no-sheen, natural look is required.
Economical No-Sheen Natural Look	Penetrating Sealer Pro-Solv®	1	700 sq.ft. (65m ²)	2 hours	Yes	Yes	Provides more limited protection than premium sealers.
Low-Medium Sheen	Seal & Finish Low Sheen	1	700 sq.ft. (65m ²)	2 hours	Yes	Yes	No stripping necessary prior to sealing. Best results on textured quarry surfaces.
High-Sheen (Interior Only)	High-Gloss Sealer	1	700 sq.ft. (65m ²)	2 hours	Yes	Yes	Recommended on rough-textured surfaces only.

Sealing

Purpose: To protect porous tile from sub-surface staining and ease ongoing maintenance.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Grout Cure Time Prior To Sealing	Expected Wear	Int.	Ext.	Notes
Premium No-Sheen Natural Look	Sealer's Choice® Gold Ultra-Solv®	1-22	700 - 1,000 sq.ft. (65m ² -95m ²)	48 hours	Up to 15 Yrs	Yes	Yes	Recommended for maximum stain protection when a no-sheen, natural look is required.
Economical No-Sheen Natural Look	Penetrating Sealer Pro-Solv®	1-2	700 - 1,000 sq.ft. (65m ² -95m ²)	48 hours	Up to 5 Yrs Up to 10 Yrs	Yes	Yes	Provides more limited protection than premium sealers.
Premium No-Sheen Darkened Color Enhancement	Seal & Finish Low Sheen	2-3	700 - 1,000 sq.ft. (65m ² -95m ²)	48 hours	Up to 15 Yrs	Yes	Yes	Use only on unsealed stone surfaces - seals the surface as it darkens. Critical to test for desired look as darkening is non-reversible.
Economical No-Sheen Darkened Color Enhancement	High-Gloss Sealer	2-3	700 - 1,000 sq.ft. (65m ² -95m ²)	48 hours	Up to 5 Yrs	Yes	Yes	Use only on unsealed stone surfaces - seals the surface as it darkens. Critical to test for non-reversible.

Maintenance

Purpose: To safely maintain a clean tile and grout surface and to preserve the tile's beauty and integrity.

Type of Maintenance	Product Options	Dilution Ratio	Expected Coverage Per Gallon (3.8 L)	Notes
Routine	Concentrated Stone & Tile Cleaner AquaKleen™	1-4oz./gallon of water (30-118ml/3.785L) Use undiluted	10,000-20,000 sq. ft. (930m ² -1,860m ²)	Highly-concentrated. Neutral pH. For regular use. Quick spray and wipe cleaning.
Periodic Heavy-Duty	Heavy-Duty Tile & Grout Cleaner Stone Deep Clean	Add up to 4 parts water	500 - 600 sq. ft. (45m ² -55m ²)	Contains no acid. Safe on tile and grout/mortar
Periodic Heavy-Duty Large Commercial Areas	1 & 2 Deep Clean	1/4 to 1/2 cup (60 - 120 ml) of powder & liquid to 2 1/2 gallons (10 L) of water.	8,000 - 32,000 sq. ft. (743m ² -2,973m ²)	Recommended for large commercial floor applications.

Always refer to product Data Sheets for complete application, use, safety, limitation and warranty information.
Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.