

## Pre-Grouting Sealing

**Purpose:** To protect porous tile from grout staining and ease grout clean-up.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Cure Time Prior To Grouting	Int.	Ext.	Notes
<b>Color Staining (if darker or different color is desired)</b>	Aqua Stain Ultra-Solv®	1	50-400 sq.ft. (5m <sup>2</sup> - 40m <sup>2</sup> )	2 hours	Yes	Yes	Dilute with up to 8 parts water for translucent look. Must be applied to unsealed Salttillo.
<b>Premium No-Sheen Natural Look</b>	Sealer's Choice® Gold Ultra-Solv®	1	300 sq.ft. (30m <sup>2</sup> )	2 hours	Yes	Yes	Use if no-sheen, natural-look is required. Low to high sheen finishes will result in easier on-going maintenance.
<b>Economical No-Sheen Natural Look</b>	Penetrating Sealer Pro-Solv®	1	300 sq.ft. (30m <sup>2</sup> )	2 hours	Yes	Yes	Provides more limited protection than premium sealers.
<b>Low-Medium Sheen</b>	Seal & Finish Low Sheen	1-2	300 sq.ft. (30m <sup>2</sup> )	2 hours	Yes	Yes	Easy reapplication. No stripping necessary. Excellent stain protection.
<b>High-Sheen (Interior Only)</b>	High-Gloss Sealer	1-2	300 sq.ft. (30m <sup>2</sup> )	2 hours	Yes	No	Interior areas only.

**Note:** If color staining is desired, Seal & Finish Low Sheen or High-Gloss Sealer is recommend for use over Aqua Mix Aqua Stain for maximum protection.

## Color Staining

**Purpose:** To protect porous Salttillo from sub-surface staining and ease ongoing maintenance.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Cure Time Prior To Grouting	Expected Wear	Int.	Ext.	Notes
<b>Color Staining (if darker or different color is desired)</b>	Aqua Stain	1-2	50 - 400 sq.ft. (5m <sup>2</sup> - 40m <sup>2</sup> )	48 N/A	N/A	Yes	Yes	Dilute with up to 8 parts water for translucent look. Must be applied to unsealed Salttillo.

## Sealing/Finishing

**Purpose:** To protect porous Salttillo from sub-surface staining and ease ongoing maintenance.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Grout Cure Time Prior To Sealing	Expected Wear	Int.	Ext.	Notes
<b>Premium No-Sheen Natural Look</b>	Sealer's Choice® Gold Ultra-Solv®	2-3	700 - 1,000 sq.ft. (65m <sup>2</sup> - 95m <sup>2</sup> )	48 hours	Up to 15 Yrs	Yes	Yes	Use if a no-sheen, natural look is required. Low to high-sheen finishes will result in easier ongoing maintenance.
<b>Economical No-Sheen Natural Look</b>	Penetrating Sealer Pro-Solv®	2-3	700 - 1,000 sq.ft (65m <sup>2</sup> - 95m <sup>2</sup> )	48 hours	Up to 5 Yrs Up to 10 Yrs	Yes	Yes	Provides more limited protection than premium sealers.
<b>Low-Medium Sheen</b>	Seal & Finish Low Sheen	3-4	700 - 1,000 sq.ft (65m <sup>2</sup> - 95m <sup>2</sup> )	48 hours	Up to 3 Yrs	Yes	Yes	Easy reapplication. No stripping necessary. Excellent stain protection.
<b>High-Sheen (Interior Only)</b>	High-Gloss Sealer	3-4	700 - 1,000 sq.ft. (65m <sup>2</sup> - 95m <sup>2</sup> )	48 hours	Up to 3 Yrs	Yes	No	Interior areas only.

## Maintenance

**Purpose:** To safely maintain a clean tile and grout surface and to preserve the tile's beauty and integrity.

Type of Maintenance	Product Options	Dilution Ratio	Expected Coverage Per Gallon (3.8 L)	Notes
<b>Routine</b>	Concentrated Stone & Tile Cleaner AquaKleen™	1-4oz./gallon of water (30-118ml/3.785L) Use undiluted	10,000-20,000 sq.ft. (930m <sup>2</sup> -1,860m <sup>2</sup> )	Highly-concentrated. Neutral pH. For regular use. Quick spray and wipe cleaning.
<b>Periodic Heavy-Duty</b>	Heavy-Duty Tile & Grout Cleaner Stone Deep Clean	Add up to 4 parts water	500 - 600 sq. ft. (45m <sup>2</sup> -55m <sup>2</sup> )	Contains no acid. Safe on tile and grout/mortar. Will remove floor finishes.

Always refer to product Data Sheets for complete application, use, safety, limitation and warranty information.  
Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.