

# Travertine - Honed

## Pre-Grouting Sealing

**Purpose:** To protect porous stone from grout staining and ease grout clean-up.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Cure Time Prior To Grouting	Int.	Ext.	Notes
<b>Premium No-Sheen Natural Look</b> Ultra-Solv™	Sealer's Choice® Gold	1	800 sq.ft. (75m <sup>2</sup> )	2 hours	Yes	Yes	Recommended in food preparation or serving areas for maximum stain protection when a no-sheen, natural look is required.
<b>Economical No-Sheen Natural Look</b>	Penetrating Sealer Pro-Solv®	1	800 sq.ft. (75m <sup>2</sup> )	2 hours	Yes	Yes	Provides more limited protection in food preparation and serving areas.
<b>Premium No-Sheen Darkened Color Enhancement</b>	Enrich'N'Seal™	1	800 sq.ft. (75m <sup>2</sup> )	2 hours	Yes	Yes	Use only on unsealed stone surfaces. Critical to test for desired look as darkening is non-reversible.
<b>Economical No-Sheen Darkened Color Enhancement</b>	Stone Enhancer	1	800 sq.ft. (75m <sup>2</sup> )	2 hours	Yes	Yes	Use only on unsealed stone surfaces. Critical to test for desired look as darkening is non-reversible.

## Sealing

**Purpose:** To protect porous stone from sub-surface staining and ease ongoing maintenance.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Grout Cure Time Prior To Sealing	Expected Wear	Int.	Ext.	Notes
<b>Premium No-Sheen Natural Look</b>	Sealer's Choice® Gold Ultra-Solv®	2	700 - 1,000 sq.ft. (65m <sup>2</sup> - 95m <sup>2</sup> )	48 hours	Up to 15 Yrs	Yes	Yes	Recommended for maximum stain protection when a no-sheen, natural look is required.
<b>Economical No-Sheen Natural Look</b>	Penetrating Sealer Pro-Solv®	2	700 - 1,000 sq.ft. (65m <sup>2</sup> - 95m <sup>2</sup> )	48 hours	Up to 5 Yrs Up to 10 Yrs	Yes	Yes	Provides more limited protection than premium sealers.
<b>Premium No-Sheen Darkened Color Enhancement</b>	Enrich'N'Seal™	1-2	1,200 sq.ft. (110m <sup>2</sup> )	48 hours	Up to 15 Yrs	Yes	Yes	Use only on unsealed stone - seals the surface as it darkens. Critical to test for desired look as darkening is non-reversible.
<b>Economical No-Sheen Darkened Color Enhancement</b>	Stone Enhancer	1-2	1,200 sq.ft. (110m <sup>2</sup> )	48 hours	Up to 5 Yrs	Yes	Yes	Use only on unsealed stone - seals the surface as it darkens. Critical to test for non-reversible.

## Maintenance

**Purpose:** To safely maintain a clean stone and grout surface and to preserve the stone's beauty and integrity.

Type of Maintenance	Product Options	Dilution Ratio	Expected Coverage Per Gallon (3.8 L)	Notes
<b>Routine</b>	Concentrated Stone & Tile Cleaner AquaKleen™	1-4oz./gallon of water (30-118ml/3.785L) Use undiluted	10,000-20,000 sq.ft. (930m <sup>2</sup> -1,860m <sup>2</sup> )	Highly-concentrated. Neutral pH. For regular use. Quick spray and wipe cleaning.
<b>Routine Countertops &amp; Walls</b>	Stone Clean & Shine Brilliance®	Use undiluted	N/A	Designed to clean & polish - helps maintain factory shine.
<b>Periodic Heavy-Duty</b>	Stone Deep Clean or Heavy-Duty Tile & Grout Cleaner	Add up to 4 parts water	500 - 600 sq. ft. (45m <sup>2</sup> -55m <sup>2</sup> )	Contains no acid. Safe on tile and grout/mortar. Removes wax-type finishes.
<b>Periodic Heavy-Duty Large Commercial Areas</b>	1&2 Deep Clean	1/4 to 1/2 cup (60-120ml) powder and liquid to 2 1/2 gallons of water.	8,000 - 32,000 sq. ft. (743m <sup>2</sup> -2,973m <sup>2</sup> )	Recommended for large commercial floor applications.

Always refer to product Data Sheets for complete application, use, safety, limitation and warranty information.  
Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.