

Travertine - Polished

Pre-Grouting Sealing

Purpose: To protect porous stone from grout staining and ease grout clean-up.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Cure Time Prior To Grouting	Int.	Ext.	Notes
Premium No-Sheen Natural Look Ultra-Solv™	Sealer's Choice® Gold	1	1,000 sq.ft. (95m²)	2 hours	Yes	Yes	Recommended in food preparation or serving areas for maximum stain protection when a no-sheen, natural look is required.
Economical No-Sheen Natural Look	Penetrating Sealer Pro-Solv®	1	1,000 sq.ft. (95m²)	2 hours	Yes	Yes	Provides more limited protection in food preparation and serving areas.
Premium No-Sheen Darkened Color Enhancement	Enrich'N'Seal™	1	1,000 sq.ft. (95m²)	2 hours	Yes	Yes	Use only on unsealed stone surfaces. Critical to test for desired look as darkening is non-reversible.
Economical No-Sheen Darkened Color Enhancement	Stone Enhancer	1	1,000 sq.ft. (95m²)	2 hours	Yes	Yes	Use only on unsealed stone surfaces. Critical to test for desired look as darkening is non-reversible.

Sealing

Purpose: To protect porous stone from sub-surface staining and ease ongoing maintenance.

Desired Result	Product Options	# of Coats	Approx. Coverage Per/Coat Per/Gal (3.8 L)	Grout Cure Time Prior To Sealing	Expected Wear	Int.	Ext.	Notes
Premium No-Sheen Natural Look	Sealer's Choice® Gold Ultra-Solv®	1-2	1,000 sq.ft. (95m²)	48 hours	Up to 15 Yrs	Yes	Yes	Recommended where maximum stain protection is required.
Economical No-Sheen Natural Look	Penetrating Sealer Pro-Solv®	1-2	1,000 sq.ft. (95m²)	48 hours	Up to 5 Yrs Up to 10 Yrs	Yes	Yes	Provides more limited protection than premium sealers.
Premium No-Sheen Darkened Color Enhancement	Enrich'N'Seal™	1-2	1,000 sq.ft. (95m²)	48 hours	Up to 15 Yrs	Yes	Yes	Use only on unsealed stone - seals the surface as it darkens. Critical to test for desired look as darkening is non-reversible.
Economical No-Sheen Darkened Color Enhancement	Stone Enhancer	1-2	1,000 sq.ft. (95m²)	48 hours	Up to 5 Yrs	Yes	Yes	Use only on unsealed stone - seals the surface as it darkens. Critical to test for non-reversible.

Finishing

Purpose: To provide and maintain a protective wear-layer and enhance the surface shine on walls and countertops.

Type of Maintenance	Product Options	Dilution Ratio	Expected Coverage	Int.	Ext.	Notes
Protect Factory Polish on Countertops and Walls	Stone Clean & Shine Brilliance®	Use undiluted to spray and buff	N/A	Yes	No	Designed to polish & clean - helps maintain factory shine. Not recommended for floors.

Maintenance

Purpose: To safely maintain a clean stone and grout surface and to preserve the stone's beauty and integrity.

Type of Maintenance	Product Options	Dilution Ratio	Expected Coverage Per Gallon (3.8 L)	Notes
Routine	Concentrated Stone & Tile Cleaner AquaKleen™	1-4oz./gallon of water (30-118ml/3.785L) Use undiluted	10,000-20,000 sq.ft. (930m²-1,860m²)	Highly-concentrated. Neutral pH. For regular use. Quick spray and wipe cleaning.
Periodic Heavy-Duty	Stone Deep Clean or Heavy-Duty Tile & Grout Cleaner	Add up to 4 parts water	500 - 600 sq. ft. (45m²-55m²)	Contains no acid. Safe on tile and grout/mortar. Removes wax-type finishes.
Periodic Heavy-Duty Large Commercial Areas	1&2 Deep Clean	1/4 to 1/2 cup (60-120ml) powder and liquid to 2 1/2 gallons of water.	8,000 - 32,000 sq. ft. (743m²-2,973m²)	Recommended for large commercial floor applications.

Always refer to product Data Sheets for complete application, use, safety, limitation and warranty information.
Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.