


# COMMERCIAL EPOXY GROUT

# CEG-2000™

## 100% Solids Epoxy

- **Easy to spread • Easy water clean-up**
  - **100% solids • Non-shrinking**
- **Highly stain and chemical resistant**
  - **Use as a grout or mortar**
  - **For joint widths 1/16" - 1/2"**



#811 White



#882 Light Beige



#880 Beige



#852 Brown



#896 Brick Red



#809 Medium Gray



#870 Dark Gray



#860 Black



Sample colors shown approximate as nearly as possible the color of the grout.

## Contractor Preferred & Industrial Tough

### CEG-2000™ COMMERCIAL EPOXY GROUT

**Meets ANSI 118.3 for Chemical Resistant, Water Cleanable, Tile Setting and Grouting Epoxy**

CEG-2000 is a 2-part blend of epoxies and aggregates that delivers a grout that's easy to work, uniform in color, and colorfast. As a mortar, it's very high in strength and shock resistance. CEG-2000 is very resistant to acids, alkalis and most solvents, while offering maximum resistance to staining and chemical attack from food, beverages, chemicals and cleaning agents.



### COVERAGE

SQ. FT. PER 2 GALLONS

| TILE SIZE              | GROUT JOINT WIDTH |      |      |      |      |
|------------------------|-------------------|------|------|------|------|
|                        | 1/16"             | 1/8" | 1/4" | 3/8" | 1/2" |
| 1" x 1" x 1/4"         | 106               | 55   | 30   | 21   | 17   |
| 2" x 2" x 1/4"         | 209               | 106  | 55   | 38   | 30   |
| 4 1/4" x 4 1/4" x 1/4" | 440               | 222  | 113  | 76   | 58   |
| 6" x 6" x 1/4"         | 619               | 311  | 158  | 106  | 81   |
| 8" x 8" x 3/8"         | 550               | 276  | 139  | 94   | 71   |
| 12" x 12" x 3/8"       | 824               | 413  | 208  | 139  | 105  |
| 16" x 16" x 3/8"       | 1098              | 550  | 276  | 185  | 139  |

Coverages are approximate and may be reduced by 10% - 20+% based on waste, spillage and project conditions.

**Coverage as Mortar:** Approximately 50 - 60 sq. ft. per 2 gallons when applied with a 1/4" x 1/4" x 1/4" square-notch trowel. 80 - 90 sq. ft. per 2 gallons when applied with a 3/16" x 5/32" v-notch trowel.



Use Custom products for a quality tile or stone installation that's covered by a Lifetime Warranty. Look for the warranty symbol on Custom packages.

No VOCs

Contains no Volatile Organic Compounds



**CUSTOM®**  
BUILDING PRODUCTS

800-272-8786

[www.custombuildingproducts.com](http://www.custombuildingproducts.com)

©2008 Custom Building Products. Nationwide manufacturing facilities.  
Printed in the U.S.A. CEGCC 5/08R BH