


### Crome Mosaic Important Notice

ONIX Crome Mosaic is coated with a very thin layer of titanium as part of the manufacturing process. Improper handling may cause irreversible damage to the mosaic. Follow the instructions carefully as they appear on the box.

The laying guidelines are the same as for other mosaics in the ONIX Collection Mosaic Tile Laying Guidelines, subject to the following exceptions.

With the following exceptions the laying guidelines for ONIX Crome are the same as for other mosaics Mosaic Tile Laying Guidelines.



- Always ensure the Crome Mosaics are stored in the original package until they are ready to be laid. When each tile is removed from the packaging ensure that the upper surface is always facing upwards to avoid any scratching and scraping. Never remove the protective film (silicone spray) until the final cleaning stage of the laying process is reached.
- For fixing purposes the following adhesives are strongly recommended - Custom Building Products **CEG 2000 100% Solids Commercial Epoxy Grout** (White), **MegaLite** (White), **ProLite** (White), **VersaBond Flex** (White) and **VersaSet** (White). Prevent any adhesive from adhering to the face of the glass during the installation process.
- Only use grouting materials exclusively based on superfine arid materials, (with an average diameter of 12 microns). Custom Building Product **PolyBlend Non-Sanded Grout** is strongly recommended.
- Remove the grout residue immediately with clear water and a soaked soft sponge.
- Do not use powdered detergent, steel wool or any abrasive materials.
- Finally remove the remains of the protective film (silicone spray) with a clean cloth, wet with acetone or steam water cleaner, before a final clean with a solution of clear warm water.
- Thereafter, for routine cleaning purposes only use **Aqua Mix Concentrated Stone & Tile Cleaner**.